

VLF-34E 34 kV VLF Tester

Very Low Frequency AC Technology

VLF & DC Output • Sheath Testing • Cable Burning

The VLF-34E is a new generation VLF AC hipot that uses a solid state design with microprocessor controls. It meets the requirements of applicable world standards regarding cable testing up to 25kV class Maintenance testing. It is light, compact, rugged, and very portable. Its sine wave output is suitable for using optional external PD and TD detection equipment. Using a **TD** and **PD option**, the VLF-34E is all that is needed for nearly all cable testing up to 25kV class.

Specifications – Solid State Design

Input Voltage: 90 Vac – 265 Vac, 50 Hz/60Hz, 5A max.

HV Output: 0-34 kVac peak/0-24 kVac rms - Sinusoidal

DC: +/- 34 kV Square wave: 34 kV Sheath Tester

Duty: Continuous Frequency: 0.1 Hz to 0.01 Hz

Load Rating: 0.5 μ F @ 0.1 Hz @ 34 kV

1.0 μF @ 0.05 Hz @ 34 kV 5.0 μF @ 0.01 Hz @ 34 kV

 μF rating increases at lower voltages Ex: 0.77 μF @ 0.1 Hz @ 22 kV peak

Metering: Voltage kV peak or RMS

Current mA peak or RMS

Calculated: Capacitance, Resistance, Flashover voltage,

Time to Failure

Size/Weight: 19.7" x 12.0" x 18", 45 lbs.

500mm x 305mm 458mm, 21 kg.

Case: Hard "Pelican" type case with extendable

handle and wheels

Lead Outputs: HV lead: 20' RG8/U, Ground 20' #2

Fault: Smart Fault Management

or shutdown on Fault

Reports: Test Records stored in non-volatile

memory or via USB memory stick

PC Interface: USB, xbee(r) wireless, RS-232/422
PC Software: Remote Control & Test Reports

Optional Tan Delta and Partial Discharge diagnostic equipment available.


ISO 9001:2008



Easy to use controls. Programmable test sequences & manual control, USB port for downloading data and for unlimited test report capture, wireless computer interface to control and download optional Tan Delta diagnostics and for remote control operation via laptop.

Cable Standards met:

IEEE 400.2-2004, IEEE 400-2001, IEC 60060-3 VDE DIN 0276-620/621, CENELEC HD 620/621







HIGH VOLTAGE, INC.

31 County Rt. 7A, Copake, NY 12516 • (518) 329-3275 • Fax: (518) 329-3271

E-Mail: sales@hvinc.com • Web: www.hvinc.com