


CURRENT MEASURING TRANSFORMERS



Current measuring transformers are used for measuring AC currents. Secondary current is 5 A, rated frequency from 50 Hz to 60 Hz. The accuracy class is 1.



ASK 31,5



ASK 61,4

TYPE	POWER	I prim/5 A	Primary cable
ASR 20.3	1 VA.. 7.5 VA	50 A.. 300 A	ø 21 mm
ASR 201.3	1 VA.. 7.5 VA	50 A.. 300 A	ø 21 mm
ASR 21.3	1 VA.. 10 VA	100 A.. 600 A	ø 22.5 mm
ASR 22.3	1 VA.. 15 VA	40 A..600 A	ø 22.5 mm
ASR 22.3 2U	2.5 VA.. 10 VA	100 A..600 A	ø 22.5 mm
ASK 205.3	1 VA..10 VA	60 A.. 400 A	20 x 5 mm, ø 17.5 mm
ASK 21.3	1 VA.. 15 VA	40 A.. 600 A	20 x 10 mm, ø 19.2 mm
ASK 231.5	1 VA.. 15 VA	50 A.. 600 A	30 x 10 mm, ø 28 mm
ASK 31.3	1 VA.. 10 VA	50 A.. 750 A	30 x 10 mm, 2 x 20 x 10 mm, ø 26 mm
ASK 31.3 2U	2.5 VA.. 15 VA	100 A..600 A	30 x 10 mm, 2 x 20 x 10 mm, ø 26 mm
ASK 318.3	1 VA.. 15 VA	60 A.. 750 A	31 x 18 mm, ø 26 mm
ASK 31.4	1.25 VA.. 15 VA	50 A.. 750 A	30 x 10 mm, 2 x 20 x 10 mm, ø 28 mm
ASK 31.4 2U	2.5 VA.. 15 VA	100 A.. 600 A	30 x 10 mm, 2 x 20 x 10 mm, ø 28 mm
ASK 31.4 3U	2.5 VA.. 15 VA	100 A.. 600 A	30 x 10 mm, 2 x 20 x 10 mm, ø 28 mm
*ASK 31.5	1 VA.. 30 VA	40 A.. 750 A	30 x 10 mm, 2 x 20 x 10 mm, ø 28 mm
ASK 31.5 2U	2.5 VA.. 15 VA	75 A.. 600 A	30 x 10 mm, 2 x 20 x 10 mm, ø 28 mm
ASK 41.3	1 VA.. 15 VA	100 A.. 800 A	40 x 12 mm, 32 x 18 mm, ø 26 mm
ASK 421.4	1 VA.. 30 VA	30 A.. 500 A	20 x 10 mm, ø 20 mm
ASK 41.4	1.25 VA.. 30 VA	50 A.. 1000 A	40 x 10 mm, 2 x 30 x 5 mm, ø 32 mm
ASK 41.4 2U	2.5 VA.. 15 VA	100 A.. 1000 A	40 x 10 mm, 2 x 30 x 5 mm, ø 32 mm
ASK 41.4 3U	2.5 VA.. 15 VA	100 A.. 1000 A	40 x 10 mm, 2 x 30 x 5 mm, ø 32 mm
ASK 412.4	1.25 VA.. 30 VA	50 A.. 800 A	40 x 10 mm, 30 x 15 mm, ø 30,5 mm
ASK 541.4	1 VA.. 30 VA	30 A.. 1000 A	40 x 10 mm, 2 x 30 x 5 mm, ø 32 mm
ASK 51.4	1.5 VA.. 30 VA	100 A.. 1250 A	50 x 12 mm, 2 x 40 x 10 mm, ø 44 mm
ASK 51.4 2U	2.5 VA.. 30 VA	200 A.. 1200 A	50 x 12 mm, 2 x 40 x 10 mm, ø 44 mm
ASK 51.4 3U	2.5 VA.. 15 VA	200 A.. 1200 A	50 x 12 mm, 2 x 40 x 10 mm, ø 44 mm
ASK 561.4	2.5 VA.. 30 VA	200 A.. 1250 A	60 x 10 mm, 2 x 50 x 10 mm, ø 44 mm
*ASK 61.4	1.5 VA.. 30 VA	200 A.. 1600 A	63 x 10 mm, 2 x 50 x 10 mm, ø 44 mm
ASK 61.4 2U	2.5 VA.. 30 VA	250 A.. 1600 A	63 x 10 mm, 2 x 50 x 10 mm, ø 44 mm
ASK 61.4 3U	2.5 VA.. 15 VA	200 A.. 1600 A	63 x 10 mm, 2 x 50 x 10 mm, ø 44 mm
ASK 63.4	1.5 VA.. 15 VA	300 A.. 2000 A	60 x 30 mm, 50 x 40 mm, ø 44 mm
ASK 63.6	1.5 VA.. 30 VA	200 A.. 2000 A	60 x 30 mm, ø 30 mm
ASK 81.4	2.5 VA.. 45 VA	400 A.. 2000 A	80 x 10 mm, 60 x 30 mm, 2 x 60 x 10 mm, ø 55 mm
ASK 81.4 2U	5 VA.. 30 VA	500 A.. 2000 A	80 x 10 mm, 60 x 30 mm, 2 x 60 x 10 mm, ø 55 mm
ASK 101.4	5 VA.. 45 VA	500 A.. 2500 A	100 x 10 mm, 2 x 80 x 10 mm, ø 70 mm
ASK 101.4 2U	5 VA.. 30 VA	600 A.. 2500 A	100 x 10 mm, 2 x 80 x 10 mm, ø 70 mm
ASK 103.3	5 VA.. 45 VA	750 A.. 3000 A	2 x 100 x 10 mm, 3 x 80 x 10 mm, ø 85 mm
ASK 123.3	5 VA.. 45 VA	1000 A.. 4000 A	123 x 30 mm, 3 x 100 x 10 mm, ø 100 mm
ASK 129.10	5 VA.. 45 VA	1000 A.. 7500 A	120 x 90 mm
WSK 30	2.5 VA.. 5 VA	1 A.. 20 A	-
WSK 40	2.5 VA.. 15 VA	1 A.. 40 A	-
WSK 60	2.5 VA.. 15 VA	5 A..75 A	-
WSK 70.6	2.5 VA.. 15 VA	25 A..150 A	-

Snap-on mounting for ASK type

Other ratings and accuracy classes by agreement.

* on stock ASK 31.5 2.5 VA 50, 75 A; 5 VA 100-600 A, ASK 61.4 10 VA 800, 1000, 1200, 1500 A

Dimensional drawings are on pages 211, 212.