

SERIES ITS

SPECIFICATION

| | |
|-----------------------|---|
| TEST STANDARD | : IS 2992 - 1987 |
| ACCURACY | : $\pm 5\%$ OVER FIRST EFFECTIVE RANGE : $\pm 10\%$ OVER SECOND EFFECTIVE RANGE |
| VOLTAGE | : $\pm 10\%$ OF RATED VOLTAGE |
| INSULATION RESISTENCE | : BETTER THAN 50 M OHMS AT 500 VOLTAGE DC |
| DIE ELECTRIC TEST | : WITHSTNDS 2 kV AC (rms). |
| SCALE LENGTH | : 70 mm (APPROX). |
| WEIGHT | : 650 GRAMS (APPROX). |
| DIEMENSIONS | : 145 x 110 x 70 mm (APPROX). |
| STANDARD ACCESSORIES | : 1. A PAIR OF TESTING LEADS 1 METER IN LENGTH ALONG WITH INSTRUMENT 2. INSTRUCTION BOOKLET 3. TEST CERTIFICTE |
| OPTIONAL ACCESSORIES | : 1. A REXINE CARRYING CASE WITH STRAP 2. A SET OF TEST LEADS 3 METER LONG |

ILLUSTRATION OF SCALE :

SELECT ANY RANGE FROM THE FOLLOWING : ILLUSTRATION OF THE SCALE

| RATED VOLTAGE | RATED RESISTENCE | MODEL NUMBER |
|---------------|------------------|--------------|
| 500 V | 100 M OHMS | ITS5010 |
| 1000V | 200 M OHMS | ITS10020 |