

## Soft Discharge Rod

## Reliable and cost effective Soft discharge rods

Damped discharge of the cable/ Device Under Test (DUT), through suitable resistor.

Range: 11kV-100kV working for maximum capacity discharge up to 6 microfarad.

Robust housing of reinforced fibreglass having protection ring and rubberised handle for proper grip.

Supplied with cushioned soft carrying case to withstand severe transport jerks and shocks.

Each rod is provided with 10sq. mm, 5 mtr flexible cable having heavy duty brass clamp for earth connection.

## Customer Service

All instruments have been designed based on safety, capability, field application, ruggedness and ease of operations. We try to offer the best possible solutions for the job.

We not only offer our after sales services to the customers through our branches / authorized agents, but also give training to the working staff of the customers under specialized training programs.

## Specifications

## SDR

| Model        | Damping Resistor | Max. Capacity discharge | Max. Working voltage (kV) | Dimensions            | Weight  |
|--------------|------------------|-------------------------|---------------------------|-----------------------|---------|
| SDR-1/11kV   | 10 K Ohm         | 6 MFD                   | 11 kV                     | Ø 32 mm x (L) 750 mm  | 1.65 Kg |
| SDR-1/35 kV  | 10 K Ohm         | 6 MFD                   | 35 kV                     | Ø 32 mm x (L) 960 mm  | 2.2 Kg  |
| SDR-1/100 kV | 20 K Ohm         | 10 MFD                  | 100 kV                    | Ø 32 mm x (L) 1800 mm | 4.5 Kg  |

Marketed by

**Aplab Limited**

APLAB House, A-5, Wagle Industrial Estate,  
Thane - 400604.

Tel. : +91-22-25821861-2-3, 25820319, 25321019

Fax : +91-22-25823137,25824456, 25831128

Email : cfl@aplab.com

www.aplab.com



18, Electronic Sadan II, MIDC, Bhosari,  
Pune 411026, Maharashtra, India.

Tel. : +91-20-27120784 / 27123176

Fax : +91-20-27121787

Email : telemtrix@vsnl.net